

HIKVISION®

Live View

Playback

Picture

Configuration

Local

System

Network

TCP/IP

DDNS

PPPoE

Port

NAT

Multicast

Lan

Wlan

NIC Type

Auto

☐ DHCP

IPv4 Address

192.168.1.211

Test

IPv4 Subnet Mask

255.255.255.0

IPv4 Default Gateway

192.168.1.1

IPv6 Mode

Route Advertisement

View Route Advertisement

IPv6 Address

IPv6 Subnet Mask

IPv6 Default Gateway

::

Mac Address

10:12:fb:95:c2:76

MTU

1500

☒ Enable Multicast Discovery

DNS Server

Preferred DNS Server

8.8.8.8

Alternate DNS Server

Domain Name Settings

©2020 Hikvision Digital Technology Co., Ltd. All Rights Reserved

HIKVISION®

Live View

Playback

Picture

Configuration

Local

System

Network

TCP/IP

DDNS

PPPoE

Port

NAT

Multicast

Lan

Wlan

☐ DHCP

IPv4 Address

192.168.1.212

✓

Test

IPv4 Subnet Mask

255.255.255.0

✓

IPv4 Default Gateway

192.168.1.1

✓

Mac Address

c0-e4-34-4f-12-50

☒ Enable Multicast Discovery

DNS Server

Preferred DNS Server

8.8.8.8

✓

Alternate DNS Server

✓

Domain Name Settings

☐ Enable Dynamic Domain Name

Register Domain Name

✓

Save

©2020 Hikvision Digital Technology Co., Ltd. All Rights Reserved

Local

System

Network

Basic Settings

Advanced Settings

Video/Audio

Image

Event

Storage

SNMP

FTP

Email

Platform Access

HTTPS

QoS

Wi-Fi

Integration Protocol

N

Platform Access Mode

Hik-Connect

☒ Enable

Server IP

litedev.eu.hik-connect.com

☐ Custom

Register Status

Offline

Verification Code

6 to 12 characters allowed, including upper-case and lower-case letters, and digits. To ensure device security, a combination with at least 8 characters of all the three above mentioned types is recommended. Note: The 6-character combination "ABCDEF" and any other case sensitive combination of this alphabetical order are not allowed.

 Save